

XFS Nozzles



Automatic shut-off nozzle for farm, 12V skid tanks and consumer pump applications.

- Strong, improved flow - up to 18 gpm / 68.1 Lpm.
- Dispenses 10 gpm / 37.8 Lpm at only 5.6 psi / 0.38 bar (unleaded nozzle).
- Nozzle is equipped with a unique Flo-Stop™ device that shuts off the nozzle if it falls from the fill tank or is raised above horizontal.
- Unleaded nozzle includes StreamShaper™ to reduce turbulence for straighter fuel flow and less splash back spillage.
- Has built-in hook and fits “holster lock” of skid tank pumps.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



Unleaded Nozzles - NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337004	New with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.0 (1.3)
337008	New without Hold Open Clip, with Full Grip Guard and Hook	3.0 (1.3)
503404	New with Three Notch Hold Open Clip and Full Grip Guard, without Hook	3.0 (1.3)
504304	Rebuilt with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.1 (1.4)
503604	Rebuilt with Three Notch Hold Open Clip and Full Grip Guard, without Hook	3.1 (1.4)

Unleaded Nozzles - BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337016	New with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.0 (1.3)
503416	New with Three Notch Hold Open Clip and Full Grip Guard, without Hook	2.9 (1.3)

Light Duty Diesel Nozzles - NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337003	New with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.2 (1.4)
337007	New without Hold Open Clip, with Full Grip Guard and Hook	3.2 (1.4)
503403	New with Three Notch Hold Open Clip and Full Grip Guard, without Hook	3.6 (1.6)
504303	Rebuilt with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.2 (1.4)
503603	Rebuilt with Three Notch Hold Open Clip and Full Grip Guard, without Hook	3.2 (1.4)

Light Duty Diesel Nozzles - BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
337015	New with Three Notch Hold Open Clip, Full Grip Guard and Hook	2.9 (1.3)
503415	New with Three Notch Hold Open Clip and Full Grip Guard, without Hook	2.9 (1.3)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon
Lever	One piece contoured steel with hard plastic cover
Inlet	¾" / 19 mm NPTF & BSP

