



## Husky Model 6310 Swivel Safe-T-Break® combination for standard fueling applications.

- Multi-plane, full 360° spherical rotation for easy movement of nozzle.
- Swivel Sync® feature to prevent separation failure in the 90° position.
- Safe-T-Break® is reconnectable and retains UL listing after reconnecting.
- Dual check valves stops fuel in both directions.
- Separates at less than 225 lbf / 1000.9 N which minimizes backlash force of separations, reducing damage to equipment.
- Wave spring helps reduce nuisance breaks due to water hammer.
- Dynamic seals have double o-ring construction for long life and low temperature performance.
- Compatible with fuels containing up to 15% alcohol.
- Compact and light weight for easy handling.
- Easier to reconnect when installed at the nozzle.
- Eliminates the need for a whip hose.

### Swivel/Safe-T-Break® Combination

| MODEL NO. | DESCRIPTION  | SHIPPING WEIGHT LBS (KG) |
|-----------|--|--------------------------|
| 6310      | ¾" M x ¾" F Multi-Plane Swivel Reconnectable Safe-T-Break® | .90 (.40)                |

### Construction

|         |                              |
|---------|------------------------------|
| Body    | Aluminum, Zinc Alloy         |
| Seals   | Fluorosilicone, Fluorocarbon |
| Springs | Stainless Steel              |
| Threads | ¾" / 19.1 mm NPTF            |

