

GREASE PUMPS

Pneumatic Industrial

Alemite Industrial Pumps can deliver hard to pump fluids and viscous lubricants up to NLGI #3. Built for continuous duty, these double acting pumps are consistent, reliable, and maintain pressure over long distances.



7784-A4

7786-A5

FEATURES:

- 4 1/4" standard air motor (6" air motor for 7795-A5, 7795-B5, 7736)
- 7784-A4 is specifically designed for heavy gear oil and lubricants up to NLGI #1
- Tote tank pumps designed for horizontal mounting and space constraints
- Recommended for pumping distances over 100 feet
- 3/4" NPTF air inlet

INCLUDES:

- Air Connector
- Quick Detach Air Coupler
- Tote tank pumps include male 3" Cam Lock Adapter for mounting pump to bulk grease container

RECOMMENDED ACCESSORIES:

- Bung Adapter (326750-B1)
- Air Hose (317811-5)

Product #	Drum Size	Material Outlet	Pump Ratio	Delivery	Follower	Cover	Operating Pressure	Muffler	Material Hose	Weight
7784-A4	400 Lb.	1/2" NPTF(f)	25:1	32 lb./minute	338912	323847-4	200 psi	324170	317882-7	68.6 Lb.
7785-A5	400 Lb.	1/2" NPTF(f)	40:1	22 lb./minute	338912	323847-4	200 psi	324170	317882-7	77 Lb.
7785-B5	120 Lb.	1/2" NPTF(f)	40:1	22 lb./minute	338804	323800-4	200 psi	324170	317882-7	67 Lb.
7786-A5	400 Lb.	1/2" NPTF(f)	75:1	12 lb./minute	338912	323847-4	100 psi	324170	317882-7	69.4 Lb.
7786-C	120 Lb.	1/2" NPTF(f)	75:1	12 lb./minute	338804	323800-4	100 psi	324170	317882-7	66.6 Lb.
7795-A5	400 Lb.	1/2" NPTF(f)	80:1	13 lb./minute	338912	323847-4	100 psi	324170	317882-7	77 Lb.
7795-B5	120 Lb.	1/2" NPTF(f)	80:1	13 lb./minute	338804	323800-4	100 psi	324170	317882-7	74.6 Lb.
7735	Bulk	1/2" NPTF(f)	10:1	73 lb./minute	NA	NA	100 psi	324170	317813-5+ 339661	57 Lb.
7736	Bulk	1/4" NPTF(f)	11:1	86 lb./minute	NA	NA	100 psi	324170	317813-5+ 339661	70 Lb.
7730	Bulk	1/2" NPTF(f)	75:1	12.5 lb./minute	NA	NA	100 psi	324170	317876-5	62 Lb.

Note: Follower, Cover and Muffler sold separately.