LD Series Electronic Meters

Dispense Meters and Control Valves

Features and Benefits

- Manual and Preset Dispense
- Dispenses in gallons, quarts, pints and liters
- Easy to read LCD display with durable switches for long life
- Rugged engineered material for superior impact resistance and long life
- Ergonomically-designed handle for optimum comfort
- Standard rigid extension kit and automatic thermal compensating nozzle
- Optional extensions available

Typical Applications

- Metered oil dispense
- Automotive dealerships
- Heavy-duty dealerships
- Fast lube centers
- Fleet service facilities
- Service shops
- For indoor use only
- In-plant

Typical Fluids Handled

- Petroleum- and synthetic-based oils
- Anti-freeze

Technical Specifications

Flow Range ⁽¹⁾	0.1 - 5 gpm (0.4 - 19 lpm)
Maximum Working Pressure	1000 psi (69 bar)
Units of measure	oints, gallons, liters (factory set to quarts)
Weight	3 lb (1.36 kg)
Inlet	1/2 in npt
Weight	
Operating Temperature Range	32 - 120° F (0 - 48.8° C)
Storage Temperature Range	-30 - 120° F (-34 4 - 48 8° C)
Storage Temperature Range Battery	Q volt alkaling
Battery Life	one year
Wetted Parts	eet pitrile rubber zine ee lee
Motor Process Legal	OO noi (C O hor) @ F anno (10 hors)
Meter Pressure Loss ⁽¹⁾	90 psi (6.2 dar) @ 5 gpin (19 ipin)
Accuracy ^(c)	±0.5%
Dimensions (without extension)	
	(28 cm L x 8.3 cm W x 8.3 cm H)
Maximum Totalizer	999,999 gallons or liters
Maximum Recorded Dispense	
Warranty	Two Years
Maximum Recorded Dispense	312668
(1) Tested in 10W oil at 70°F. Flow rates vary with fluid pressure, temperature, viscosity, inlet fitting and	
(2) @ 2.5 gpm (9.5 lpm) @ 70° F (21° C) with 10 wt. oil and 1 gal (3.8 l) dispensed.	•

Ordering Information

May require re-calibration. Out-of-box accuracy $\pm 1.25\%$. Not recommended for in-line installation.

LDM5 Manual Dispense Meters	
1/2 in npt(f) swivel, flexible extension and automatic nozzle for oil and anti-freeze	
1/2 in npt(f) swivel, rigid extension, trigger guard/boot and automatic nozzle for oil and anti-freeze	
1/2 in npt(f) swivel, flexible extension, trigger guard/boot and automatic nozzle for oil and anti-freeze	
LDP5 Preset Dispense Meters	
1/2 in npt(f) swivel, flexible extension and automatic nozzle for oil and anti-freeze	
1/2 in npt(f) swivel, rigid extension, trigger guard/boot and automatic nozzle for oil and anti-freeze	
1/2 in npt(f) swivel, flexible extension, trigger guard/boot and automatic nozzle for oil and anti-freeze	

