

# Power and Light Cord Reels | Series L4000 / L5000 / L7000

Made  
in USA



L 4050 163 X



L 4545 123 7



L 4545 123 9G

- ✓ Compact for critical space requirements
- ✓ Durable abrasion and corrosion resistant baked-on powder coat finish
- ✓ Engineered for industrial use
- ✓ Adjustable cord stop
- ✓ All models supplied with cord are complete with a 5 foot pigtail and three-prong plug (except flying lead reels)
- ✓ Wall, ceiling or bench mount

Model with Cord	Cord Ending	Cord Specifications				Volts	Amps	Shipping Weight		Size Index #
		AWG	mm	# Cond.	ft m			lbs	kg	
Q5 L 4035 163 3	Single Receptacle	16	1.33	3	35 11	SJTOW	125	13	25 11	1
Q5 L 4050 163 3	Single Receptacle	16	1.33	3	50 15	SJTOW	125	13	26 12	1
Q5 L 4545 123 3	Single Receptacle	12	3.32	3	45 14	SJE00W	125	15	27 12	1
Q5 L 5550 123 3	Single Receptacle	12	3.32	3	50 15	SJE00W	125	15	44 20	3
Q5 L 4545 123 3A	Single Receptacle	12	3.32	3	45 14	SJE00W	125	20	28 13	1
Q5 L 5550 123 3A	Single Receptacle	12	3.32	3	50 15	SJE00W	125	20	44 20	3
Q5 L 4545 123 3B	Twist Lock Connector	12	3.32	3	45 14	SJE00W	125	20	28 13	1
Q5 L 5550 123 3B	Twist Lock Connector	12	3.32	3	50 15	SJE00W	125	20	44 20	3
Q5 L 5750 103 4	R.V. Plug	10	5.37	3	50 15	SOOW	125	30	50 23	4
Q5 L 4545 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJE00W	125	15	29 13	1
IN L 4545 123 7A	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJE00W	125	20	29 13	1
IN L 4545 123 7B	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJE00W	125	20	29 13	1
Q5 L 5550 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	50 15	SE00W	125	15	45 20	3
Q5 L 4050 163 9	Triple Tap	16	1.33	3	50 15	SJE00W	125	13	26 12	1
Q5 L 4545 123 9	Triple Tap	12	3.32	3	45 14	SJE00W	125	15	28 13	1
IN L 4545 123 9G	Triple Tap w/GFCI(F)	12	3.32	3	45 14	SJE00W	125	15	29 13	1

**For indoor non-weather tight applications only.** All models UL listed at 125 Volt 60 HZ single phase. \*The GFCI Receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. Reference page 4 for guide arm positions. **NOTE:** Swing brackets should be used if cords are pulled at more than 45°, see page 47.

## Cord Options

	<b>#3 - Single Receptacle</b> Single 15 AMP with clamp type strain relief for both 16 AWG and 12 AWG cord. NEMA 5-15R
	<b>#3A - Single Receptacle</b> Single 20 AMP. NEMA 5-20R
	<b>#3B - Twist Lock Connector</b> Single 20 AMP with twist lock connector. NEMA L5-20R
	<b>#4 - R.V. Plug</b> Male rubber plug used with recreational vehicles (RV's).
	<b>#7/7A/7B - Duplex Outlet Box</b> Duplex outlet box with flip-top lid. GFCI protection on #7 and 7A.
	<b>#9/9G - Triple Tap</b> Molded triple tap. GFCI protection on #9G only.
	<b>X - Flying Lead</b> Bare cord or cable endings and conduit box.

Flying Lead Model with Cord	Model No Cord	Cord Specifications				Volts/ Amps	Volts/ Amps	Shipping Weight*		Size Index #
		AWG	mm	# Cond.	ft m			lbs	kg	
L 4050 163 X	L 4000	16	1.33	3	50 15	SJE00W	125 / 13	22 10	1	
-----	L 4100	16	1.33	4	40 12	SJE00W	125 / 13	22 10	1	
IN L 4545 123 X	L 4500	12	3.32	3	45 14	SJE00W	125 / 20	22 10	1	
-----	L 5000	10	5.27	3	35 11	SO	125 / 30	22 10	1	
-----	L 5400	12	3.32	3	35 11	SJE00W	125 / 13	29 13	2	
L 5550 123 X	L 5500	12	3.32	3	50 15	SE00W	125 / 20	22 10	3	
L 5550 124 X	-----	12	3.32	4	50 15	SE00W	-----	600 / 16	44 20	3
L 5750 103 X	L 5700	10	5.27	3	50 15	SE00W	125 / 30	22 10	4	
-----	L 7000	6	13.3	4	35 11	SOOW	-----	220 / 45	41 19	**
L 7050 104 X	-----	10	5.27	4	50 15	SE00W	-----	600 / 20	65 29	**

**For indoor non-weather tight applications only.** All models UL listed at 125 Volt 60 HZ single phase. \*Weight of model without cord. \*\*Refer to reelcraft.com. Reference page 4 for guide arm positions.

**Available Options**

**Mounting Brackets**  
See page 47



**Optional Roller Guide**  
See page 47



**Replacement Bumpers**  
See page 49



Models listed with an icon can ship same day upon request when the order is received by 11:30 AM Eastern Time for quantities of 10 or fewer.

Indiana Warehouse

Indiana & California Warehouses

California Warehouse

Canadian Warehouse