

Automatic shut-off nozzle for full-service and self-service stations.

- X nozzle shuts off when the gas tank is full.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Equipped with a unique Flo-Stop™ device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper™* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.



New Unleaded Nozzles

| MODEL NO. | DESCRIPTION | SHIPPING WEIGHT LBS (KG) |
|-----------|---|--------------------------|
| 159404 | with Three Notch Hold Open Clip | 3.0 (1.3) |
| E159404 | with Three Notch Hold Open Clip and Mate Guard | 3.1 (1.3) |
| 159408 | without Hold Open Clip | 3.0 (1.3) |
| E159408 | without Hold Open Clip, with Mate Guard | 3.0 (1.3) |
| 159424 | with Three Notch Hold Open Clip and Sightglass | 2.9 (1.3) |
| 159454 | with Three Notch Hold Open Clip and Flo-Equalizer™ | 3.0 (1.3) |
| 159458 | without Hold Open Clip, with Flo-Equalizer™ | 3.0 (1.3) |
| 159464 | with Three Notch Hold Open Clip and Waffle Splash Guard | 2.7 (1.2) |
| 159468 | without Hold Open Clip, with Waffle Splash Guard | 2.7 (1.2) |

New Light Duty Diesel Nozzles

| MODEL NO. | DESCRIPTION | SHIPPING WEIGHT LBS (KG) |
|-----------|---|--------------------------|
| 159403 | with Three Notch Hold Open Clip | 3.1 (1.4) |
| E159403 | with Three Notch Hold Open Clip and Mate Guard | 3.1 (1.4) |
| 159407 | without Hold Open Clip | 3.0 (1.3) |
| E159407 | without Hold Open Clip, with Mate Guard | 3.0 (1.3) |
| 159453 | with Three Notch Hold Open Clip and Flo-Equalizer™ | 3.1 (1.4) |
| 159457 | without Hold Open Clip, with Flo-Equalizer™ | 3.1 (1.3) |
| 159463 | with Three Notch Hold Open Clip and Waffle Splash Guard | 2.8 (1.2) |
| 159467 | without Hold Open Clip, with Waffle Splash Guard | 2.8 (1.2) |

Construction

| | |
|---------|---|
| Body | One piece die cast aluminum |
| Seals | Fluorocarbon |
| Packing | Double o-ring seal protected by fiber reinforced Teflon |
| Lever | One piece contoured steel with hard plastic cover |
| Inlet | ¾" / 19 mm NPTF |

