

# 1GS Nozzles



**Automatic shut-off nozzle for farm, 12V skid tanks, large pumps with or without air eliminators and commercial applications.**

- 1GS nozzle shuts off when the gas tank is full.
- Equipped with unique Flo-Stop™ device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- Not for use with gravity tanks.
- Not legal for retail dispensing applications.



### New Unleaded Nozzles w/ NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045704	with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.6 (1.6)
045708	without Hold Open Clip with Full Grip Guard and Hook	3.6 (1.6)
045759	with Three Notch Hold Open Clip, Full Grip Guard, Hook and Reducer Bushing	3.6 (1.6)

### New Unleaded Nozzles w/ BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045716	with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.6 (1.6)
045720	without Hold Open Clip with Full Grip Guard and Hook	3.6 (1.6)

### New Light Duty Diesel Nozzles w/ NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045703	with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.6 (1.6)
045707	without Hold Open Clip with Full Grip Guard and Hook	3.6 (1.6)
045761	with Three Notch Hold Open Clip, Full Grip Guard, Hook and Reducer Bushing	3.6 (1.6)

### New Light Duty Diesel Nozzles w/ BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045715	with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.6 (1.6)
045719	without Hold Open Clip with Full Grip Guard and Hook	3.6 (1.6)

### New Heavy Duty Diesel Nozzles w/ NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045709	with Three Notch Hold Open Clip, Full Grip Guard and Hook without Flo-Stop™	3.6 (1.6)
045710	with Three Notch Hold Open Clip, with Full Grip Guard, and Hanging Hook	3.6 (1.6)

### New Heavy Duty Diesel Nozzles w/ BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
045738	with Three Notch Hold Open Clip, Full Grip Guard and Hook	3.6 (1.6)

### Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon
Lever	One piece contoured steel with hard plastic cover
Inlet	1" / 25.4 mm NPTF

