

Standard Swivels



Husky

GENERAL FUELING PRODUCTS

9-1

SWIVELS

For standard fueling applications.

All Husky Multi-Plane Swivels

- Compatible with unlead, diesel, and Ethanol blends through E10.
- Compact and light weight for easy handling.
- High flow rates due to laminar flow design.
- High strength step shoulder bearing diameters and impact absorbing stops.

Model 2950 Restricted Swivel

- Multi-Plane, 210° spherical rotation at the swivel nut.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

All Weather Swivels

- Multi-Plane, Full 360° spherical rotation for easy movement of nozzle.
- Double o-ring seals at each swivel provide long life at low temperatures (-40° F/C).

Warm Weather Swivels

- Multi-Plane, Full 360° spherical rotation for easy movement of nozzle.
- Double o-ring seals at each swivel provide long life at high temperatures (482° F / 250° C).



Model 0352



Model 0350



Model 2272

All Weather NPTF

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
0350	¾" M x ¾" F Swivel	.50 (.22)
0352	1" M x ¾" F Swivel	.66 (.29)
0355	¾" M x ¾" F Black Swivel	.49 (.22)
0356	1" M x ¾" F Black Swivel	.66 (.29)
2272	¾" M x ¾" F 90° Swivel	.38 (.17)
2950	¾" M x ¾" F Restricted Swivel	.50 (.22)

Warm Weather NPTF

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
0350W	¾" M x ¾" F Swivel	.50 (.22)
0352W	1" M x ¾" F Swivel	.66 (.29)
All Weather BSPP		
1491	¾" M x ¾" F BSPT Swivel	.50 (.22)
3590	¾" M x ¾" F BSPP Swivel	.60 (.27)
3590A	¾" M x ¾" F BSPP Swivel with Atex Certification	.60 (.27)
2771	¾" M x ¾" F 90° BSPP Swivel	.38 (.17)
2771A*	¾" M x ¾" F 90° BSPP Swivel with Atex certification	.38 (.17)

Warm Weather BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3590W	¾" M x ¾" F BSPP Swivel	.60 (.27)

Construction

ALL WEATHER

Body	High Aluminum Zinc Alloy
Inner O-ring	Fluorosilicone
Outer O-ring	Fluorocarbon

WARM WEATHER

Body	High Aluminum Zinc Alloy
Inner O-ring	Fluorocarbon
Outer O-ring	Fluorocarbon

