



Control valves - grease

Lincoln control valves, meters and accessories provide the durability and precision you need for your lubrication systems.

Model 740 heavy-duty high-pressure

- 7 500 psi (517 bar) maximum operating pressure
- Precision-machined, all steel handle, body and guard bracket provides durability and longevity
- Unique, precision control inlet check valve provides ease of handle operation even with increase in pressure
- Knurled handle for positive grip
- Handy trigger guard prevents pinching
- Reversible inlet check seat and hydraulic jaws provide double life
- Balanced design reduces user fatigue
- Lubricant inlet 1/4 in. NPT (f); outlet 1/8 in. NPT (f)
- Easily repaired for extended life

Model 3050 high-volume high-pressure


Same as 740 except with 3/8 in. NPT (f) lubricant inlet for use with Lincoln volume high-pressure swivels and hose.

Model 82157 repair parts kit

For control valves models 740 and 3050.

High-pressure grease control valves

Model	Description	Control valve	Thread size	Extension	Coupler
_	-	_	in.	_	_
740 3050	Heavy-duty, high-pressure High-volume, high-pressure	82393 81495	¹ / ₄ NPT (f) ³ / ₈ NPT (f)	Rigid tube Rigid tube	5845 5845



WARNING!

For safe and proper use, always consult instructions accompanying product. See Safety Warning Information for appropriate warnings.

Model 85021 kit

Consists of model 740 control valve and model 81387 universal "z" swivel.

Model 82158 repair kit

Repair parts kit for model 81387 standard universal swivel.