

Maxxim™ Premier Plus

Application:

Maxxim Premier Plus incorporates a Venturi pump in the protected confines of the inner fuel hose coupling to keep the vapor path open in the outer hose. As gasoline flows through the Venturi pump, gasoline accumulating in the bottom loop of the vapor hose is collected and returned to the fuel hose. C.A.R.B. and UL 330 approved.

Construction:

Tube: Nitrile synthetic rubber (ORS)

Cover: Chemivic™ synthetic rubber (ORS), thermoplastic outer with textile reinforcement and wire helix.

Reinforcement: Braided (1) steel wire

Temperature Range: -40°F to 140°F (-40°C to 60°C)


Packaging: Coupled lengths only, 6 pieces per box

Branding: Not branded

Couplings: Available only as factory coupled assembly.

Non-Stock/Sizes: For special production run minimum requirements, contact Customer Service.

Order Codes: 532-365-441 532-365-641 (EVR)



ID		ID-INNER HOSE		NOM. OD-INNER HOSE		WEIGHT-INNER HOSE	
in.	mm	in.	mm	in.	mm	lbs./ft.	kg/m
1 1/4	31.75	5/8	15.9	0.85	21.6	0.22	0.33

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2011 Veyance Technologies, Inc. All Rights Reserved.