

Redwing® Fuel Oil

Application:

Redwing Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

Construction:

Tube: Nitrile synthetic rubber (ORS)

Cover: Red Chemivic™ synthetic rubber (smooth finish) (ORS)

Reinforcement: Braided (2) synthetic yarn

Temperature Range: -40°F to 140°F (-40°C to 60°C)

Packaging: Reels, cut lengths, and coupled lengths

Branding: Continuous brand 1" (25.4 mm) 2 BD Redwing Fuel Oil by Goodyear™ Made in U.S.A.

Couplings: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non-Stock/Sizes: Contact Customer Service for special production run minimum requirements.

Order Codes: 532-016



ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm	in.	mm	psi	MPa	lbs./ft.	kg/m
1	25.4	1.50	38.1	250	1.72	0.57	0.85
1-1/4	31.8	1.80	45.7	250	1.72	0.65	0.97
1-3/8	34.9	1.88	47.8	250	1.72	0.70	1.04
1-1/2	38.1	2.10	53.3	250	1.72	0.92	1.37

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2011 Veyance Technologies, Inc. All Rights Reserved.